

FASTRON XP SERIES

FASTRON XP SERIES is a high performance gasoline engine oil.

TYPICAL CHARACTERISTICS					
Characteristic	Test Method	FASTRON XP 5W-30	FASTRON XP 10W-30	FASTRON XP 10W-40	FASTRON XP 15W-40
SAE Viscosity Grade	-	5W-30	10W-30	10W-40	15W-40
Density at 15 °C, kg/l	ASTM D - 4052	0.8560	0.8600	0.8626	0.8627
Kinematic Viscosity, at 40 °C, cSt	ASTM D - 7279	64.53	69.02	96.85	99.11
	ASTM D - 7279	10.96	11.03	14.87	14.49
at 100 °C, cSt					
Viscosity Index	ASTM D - 2270	162	151	161	151
ASTM Colour	ASTM D - 1500	L 2.5	L 2.5	L 2.0	L 2.5
Flash Point, °C	ASTM D - 92	242	248	240	252
Pour Point, °C	ASTM D - 5950	-33	-30	-30	-24
Total Base Number, mgKOH/g	ASTM D - 2896	7	7	7	7

PERFORMANCE LEVEL

FASTRON XP SERIES meets performance level of API SN/CF.

SUPERIORITIES

- Excellent oxidation stability that gives durable performance.
- Provides engine cleanliness and protection from excessive wear.

APPLICATION

FASTRON XP SERIES is recommended for modern car generation from the leading car manufacturers, that operate under extreme condition.

HEALTH AND SAFETY

Please contact our Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7190/5. Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or email: hsse.ptpl@pertamina.com