



PRODUCT DATA SHEET

TRUCK & FARM GREASE

Product Description

Truck N Farm Grease (Red) is a premium, high melting point lithium complex grease. It is a high temperature, extremely tacky grease designed to meet the exacting demands of heavy duty automotive, agricultural and industrial applications.

Truck N Farm Grease (Red) formulation features include additives that provide extreme pressure (EP) and anti-wear (AW) protection plus tackiness and adhesiveness agents that resist fling-off to allow the grease to stay-put under high speed and high-water pressure conditions. In addition to its EP, AW and exceptional water resistance properties.

Truck N Farm Grease (Red) also provides a high level of oxidation, rust and corrosion protection. **Truck N Farm Grease (Red)** is a special grease with advanced component technology that will provide outstanding service in the most demanding applications particularly for expensive and key equipment. The state-of-the-art equipment and procedures employed to manufacture **Truck N Farm Grease (Red)** provides this grease with a high degree of mechanical and storage stability. It will not breakdown under high mechanical stress. In storage it will not alter consistency or release oil.

Application

Truck N Farm Grease (Red) is recommended for use in automotive, mining, agricultural and industrial applications where high temperatures, high loads and water spray or ingress are encountered. **Truck N Farm Grease (Red)** is suitable for rolling element bearings, plain bearings, chassis parts, pins, gears and couplings. The recommended operating temperature range is from -6°C to 170°C . **Truck N Farm Grease (Red)** can endure higher temperatures for short periods or if the lubrication frequency is increased.

Benefits

- Excellent resistance to water spray & washout
- Reduced wear under high or shock loads
- Superior protection against rust and corrosion
- High temperature capability
- Excellent mechanical stability
- Outstanding storage stability
- Lead, Chlorine, Nitrite & Aromatic Extract free
- Resistant to fling-off



PRODUCT DATA SHEET

TRUCK & FARM GREASE

Health, Safety & Environmental

This product is classified as non-hazardous. No special precautions are required if employed and handled in accordance to normal practice for this type of product. Good personal hygiene is recommended when handling this product. After any spills or personal contact, the skin area should be washed with soap and water. Clothing should be laundered. Additional health, safety and environmental information is available in the Material Safety Data Sheet which can be obtained by contacting North Queensland Independant Fuel Services at admin@nqifs.com.au

Typical Characteristics

NLGI Grade	2
Soap/Thickener type	Lithium Complex
Colour	Red
Worked Penetration	280
Drop Point, °C	275
Oil Viscosity cSt @ 40 °C	1900
4-Ball Weld, kg	400
4-Ball Weld Scar (mm)	0.4
ASTM Water Spray Off, wt%	25

AVAILABLE IN PACK SIZES:	180kg
	20kg
	2.5kg
	420gram cartridges

Due to continual product research and development, the information contained herein is subject to formulation changes without notice.

OCTOBER 2019.